

Pool Mate

pH Down

ph DECREASER



poolwater balancer

• *Lowers pH of Pool Water*

Active Ingredient:

Sodium Bisulfate.....92%
Inert Ingredients.....8%
Total.....100%

KEEP OUT OF REACH OF CHILDREN
DANGER: POISON

CAUSES SEVERE BURNS - CONTAINS SODIUM BISULFATE.
See first aid and additional precautions on back panel.

2.5 lb

DIRECTIONS FOR USE

Always add this product to water. Do not add water to this product. Do not mix with other chemicals. Do not apply near metal fittings or near pool skimmer. Do not handle this product with bare hands. Use gloves or thoroughly clean dry utensils.

For Pools With High pH

Test the water with a test kit to determine the pH. If the pH is above 7.6, this product will decrease the pH. In a plastic pail of pool water, pre-dissolve the required amount of product as listed below. Do not add water to the product. Always add the product into the water. Simply pour the dissolved product onto the surface of the water. Keep the filter running to ensure dispersion throughout the pool and then test again 2 hours later. If the pH reading is still above 7.6, repeat the dosage until the pH reaches the range of 7.4-7.6. If the pH is below 7.4, do not add this product. Do not apply near metal fittings. Do not apply into the skimmer, through the pump or without the filter running.

For Pools With High Total Alkalinity

Ideal alkalinity range is 80-120 ppm for marcite, painted, tile or exposed aggregate pools; 120-140 ppm for vinyl pools; and 70-100 ppm for fiberglass pools. If alkalinity is high, predissolve the required amount of product listed below in one spot at the deep end of the pool away from walls and metal fixtures. Repeat each day until desired total alkalinity is reached.

HOW TO LOWER pH USING THIS PRODUCT

ACID DEMAND	GALLONS IN POOL		
	5,000	10,000	20,000
1	6.2 oz.	12.3 oz.	1.5 lbs.
2	12.3 oz.	1.5 lbs.	3.1 lbs.
3	1.2 lbs.	2.3 lbs.	4.6 lbs.
4	1.6 lbs.	3.1 lbs.	6.7 lbs.
6	2.3 lbs.	4.6 lbs.	9.2 lbs.
8	3.1 lbs.	6.2 lbs.	12.3 lbs.
10	3.9 lbs.	7.7 lbs.	15.4 lbs.

HOW TO LOWER TOTAL ALKALINITY USING THIS PRODUCT

ACID DEMAND	GALLONS IN POOL		
	5,000	10,000	20,000
10 ppm	1.1 lbs.	2.2 lbs.	4.3 lbs.
20 ppm	2.2 lbs.	4.3 lbs.	8.6 lbs.
30 ppm	3.2 lbs.	6.5 lbs.	12.9 lbs.
40 ppm	4.3 lbs.	8.6 lbs.	17.2 lbs.

PRECAUTIONARY STATEMENTS

DANGER. POISON. Contains sodium bisulfate. CAUSES SEVERE BURNS. HARMFUL IF SWALLOWED. Avoid contact with eyes, skin and clothing. Avoid breathing dust and use adequate ventilation. Wear goggles and use rubber gloves when handling. Wash thoroughly after handling. Do not mix with any chlorine products or other household chemicals.

FIRST AID

IN CASE OF CONTACT WITH SKIN: Brush off excess chemical and flush skin with water for 15 minutes. Remove contaminated clothing and shoes. Call a physician if irritation persists. Clean clothing and shoes before reusing.

IN CASE OF CONTACT WITH EYES: Flush eyes immediately for 15 minutes with large quantity of water. Call a physician.

IF SWALLOWED: Drink a large quantity of water. Follow with milk of magnesia, vegetable oil or beaten eggs. Never give anything by mouth to an unconscious person. CALL A PHYSICIAN.

IF INHALED: Remove to fresh air. Provide oxygen if necessary. If breathing difficulties persist, call a physician.

STORAGE AND DISPOSAL

Store closed container in a cool, dry and well-ventilated space.
When container is empty, rinse thoroughly with water, wrap securely in newspaper and place in trash collection.

CA Reg. No. 46043-50014

In Case of Emergency Call: 1-800-255-3924

