

Pool Mate

Concentrated Filter Cleaner

For Sand, Cartridge and D.E. Filters

Improves Filter Efficiency!

**Cuts away grease, body oils,
mineral deposits, scale and
suntan lotion**

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

See back panel for statement of practical treatment
and additional precautionary statements.

1-2702 L1117PH

1 qt

This liquid filter cleaner greatly improves filter life and efficiency. It is specially made to cleanse suntan oil and grease, as well as scale and mineral deposits from pool and spa filters of all types: cartridge, sand, and D.E. Regular use of this product will assure proper filtration.

DIRECTION FOR USE

When preparing or using this product, take care not to splash, drip or use on surfaces such as ceramic tile, linoleum, Formica brand counter surfaces, carpeting, etc. as etching or discoloration of these surfaces may take place. This product is intended for use as a pool filter cleaner.

SAND FILTERS: Turn off inlets and outlets for all chemical feeders. Close main drain and place filter in backwash position. Slowly add one quart Filter Cleaner through skimmer while backwashing. Filter Cleaner can also be added through the sand fill port. Run filter until product begins to come out of the backwash water or until the product is seen through a filter viewing cell. Soak filter for 16-24 hours. After soaking, backwash filter until water comes out clean and foam clears. Reverse procedure and start normal filter operation. For sand filters containing more than 300 pounds of sand, add two quarts Filter Cleaner.

CARTRIDGE FILTERS: Stop filter operation. Bleed off excess pressure through the filter safety valve. Open filter unit, remove cartridge from filter, and rinse excess loose dirt with a water hose from top to bottom. Place cartridge into a container of appropriate size and add 1 quart Filter Cleaner and 5 gallons water. Make sure filter unit is completely covered by the cleaner. Soak 16-24 hours. After soaking, rinse with hose at maximum pressure to remove excess Filter Cleaner or until foam residue is completely washed off. Re-install cartridge and resume normal filter operation.

DIATOMACEOUS EARTH FILTERS: Stop filter operation. Bleed off excess pressure through safety valve. Remove filter elements (grids) from filter and rinse off excess dirt with a hose from top to bottom. Place grids in a bucket and add 1 quart Filter Cleaner and 5 gallons water. Make sure grids are fully immersed in cleaner. Soak 16-24 hours. After soaking, rinse out excess Filter Cleaner with hose to maximum pressure. Re-install grid and add new filter media. Resume normal filter operation.

WARNING

KEEP OUT OF REACH OF CHILDREN

Irritant to eyes and mucous membranes. Avoid contact with skin, eyes, or clothing. Harmful if swallowed. Do not inhale or swallow. Do not mix with chlorine-type bleaches or other household chemicals.

FIRST AID

EYE CONTACT: Flush thoroughly with plenty of water for at least 15 minutes. Get prompt medical attention.

IF SWALLOWED: DO NOT INDUCE VOMITING. If conscious, give 1 to 2 glasses of water and call a physician immediately. Never give anything by mouth to an unconscious victim.

SKIN CONTACT: Flush area with plenty of water, then with soap and water. If irritation persists, get medical attention. Remove and wash clothing before reuse.

**In Case of Emergency,
Call 1-800-255-3924**

Rev No. 1117
103-018013P12
998-PM1300G01



32oz. —
30 —
28 —
26 —
24 —
22 —
20 —
18 —
16 —
14 —
12 —
10 —
8 —
6 —
4 —
2oz. —

(These gradations are approximate)